

Product Data Sheet

ATF D IV

Description and Applications

Saheli ATF D IV is a high performance automatic transmission fluid for all General Motors and Ford automatic transmissions requiring DEXRON®-III G or MERCON® quality fluids respectively. The specially selected performance additives and base oils in **Saheli ATF D IV** provide improved thermo-oxidative stability, friction retention properties, corrosion and rust protection, foam control and seal compatibility.

Features and Benefits

- Improved thermo-oxidative stability, wear protection and resistance to chemical deterioration protect against degradation at high operating temperatures and helps in maintaining the efficiency of the transmission system.
- Extremely high Viscosity Index ensures adequate lubrication in both high operating and low starting temperatures and controlled frictional properties provide smooth transmission and good shift performance while better foam control leads to smooth and lasting shift feel and reduces fluid loss.
- Improved protection against rust and corrosion and superior Low temperature pumpability and circulation ensures good cold start performance and is compatible with all common seal materials reduces possibility of oil leakage.

Specifications

GM DEXRON® III G
FORD MERCON® IV

Test Parameters	Test Method	Typical Results
Density @ 29.5°C gm/cm ³	ASTM D4052	0.8649
Viscosity Index	ASTM D2270	153
Viscosity @ 100°C (cSt)	ASTM D 445	6.020 mm ² /s
Viscosity @ 40°C (cSt)	ASTM D 7042	29.92 mm ² /s
Color	ASTM D 1500	Red
Pour Point °C	ASTM D 97	-45
Flash Point (COC) °C	ASTM D 92	214